

intAct Bike-Power Gel

Motorcycle batteries | completely maintenance free
Sealed gel block batteries



intAct
Battery-Power

intAct Bike-Power Gel

Motorcycle batteries | completely maintenance free
Sealed gel block batteries

The intAct Bike-Power Gel series is our top quality product among motorcycle batteries.

We specially developed this series for the latest motorcycles equipped with a variety of electrical loads and ABS. By combining the fibre separators and the electrolyte set in gel, we achieved an improved starting performance (up to 30 % better

performance compared to traditional motorcycle batteries). Approximately 90 % of all common motorcycle batteries are covered by more than 35 different battery types. Furthermore, the low self-discharge and outstanding shock resistance of the batteries are impressive.



Battery	Japan-Code	Volt	Capacity	Cold cranking amper	Length mm	Width mm	Height mm	Position of terminal	Terminal
GEL12-4A-BS	YTR4A-BS	12	2,5 AH (c20)	60 A (EN)	113	48	85	plug	L
GEL12-4L-B	YB4L-B, 50411	12	4 AH (c20)	60 A (EN)	120	70	92	0	A
GEL12-4L-BS	YTX4L-BS, 50314	12	3 AH (c20)	60 A (EN)	113	70	86	0	A
GEL12-5L-BS	YTX5L-BS, 50412	12	4 AH (c20)	70 A (EN)	113	70	105	0	A
GEL12-5ZS	YTZ5-S	12	4 AH (c20)	70 A (EN)	113	70	85	0	J
GEL12-6ZS	YTZ6-S	12	5 AH (c20)	70 A (EN)	113	70	105	0	J
GEL12-7A-BS	YTX7A-BS, 50615	12	6 AH (c20)	120 A (EN)	150	87	94	1	A
GEL12-7B-4	YT7B-4, GT7B-4	12	6 AH (c20)	120 A (EN)	150	65	92	1	J
GEL12-7L-BS	YTX7L-BS, 50614	12	6 AH (c20)	120 A (EN)	114	71	131	0	A
GEL12-7Z-S	YTZ7-S	12	6 AH (c20)	120 A (EN)	113	70	105	0	J
GEL12-9-4B-1	12N9-4B1, 50914	12	9 AH (c20)	170 A (EN)	137	76	140	1	B
GEL12-9B-4	YT9B-4, GT9B-4	12	8 AH (c20)	170 A (EN)	150	65	102	1	J
GEL12-9-BS	YTX9-BS, 50812	12	8 AH (c20)	170 A (EN)	150	87	105	1	A
GEL12-10B-4	YT10B-4, YTZ10-S	12	8,5 AH (c20)	200 A (EN)	150	87	96	1	J
GEL12-12A-4A1	12N12A-4A-1, 51211	12	12 AH (c20)	210 A (EN)	135	81	161	1	B
GEL12-12A-BS	YTX12A-BS, 51013	12	10 AH (c20)	210 A (EN)	150	87	105	1	J
GEL12-12AL-A	YB12AL-A, 51213	12	12 AH (c20)	210 A (EN)	135	81	161	0	D
GEL12-12B-4	YT12B-4, GT12B-4	12	10 AH (c20)	210 A (EN)	150	69	130	1	J
GEL12-12-BS	YTX12-BS, 51012	12	10 AH (c20)	210 A (EN)	150	87	132	1	A
GEL12-12Z-S	YTZ12-S	12	11 AH (c20)	210 A (EN)	150	87	109	1	J
GEL12-14B-4	YT14B-4, GT14B-4	12	12 AH (c20)	250 A (EN)	150	69	145	1	J
GEL12-14-BS	YTX14-BS, 51214	12	12 AH (c20)	250 A (EN)	150	87	147	1	A
GEL12-14L-A2	YB14L-A2, 51411	12	14 AH (c20)	250 A (EN)	135	91	167	0	D
GEL12-14ZS	YTZ14-S	12	11,5 AH (c20)	250 A (EN)	150	87	110	1	J
GEL12-16AL-A2	YB16AL-A2, 51616	12	16 AH (c20)	280 A (EN)	205	71	164	0	F
GEL12-16-B	YB16-B, 51912	12	19 AH (c20)	280 A (EN)	176	101	156	1	B
GEL12-16L-B	YB16L-B, 51911	12	19 AH (c20)	280 A (EN)	176	101	156	0	B
GEL12-20-BS	YTX20-BS, 82001	12	18 AH (c20)	300 A (EN)	175	87	155	1	A
GEL12-20L-BS	YTX20L-BS, 82000	12	18 AH (c20)	300 A (EN)	175	87	155	0	A
GEL12-N50-18L-A	Y50-N18L-A, 52012	12	20 AH (c20)	300 A (EN)	206	91	164	0	C

Battery	Japan-Code	Volt	Capacity	Cold cranking amper	Length mm	Width mm	Height mm	Position of terminal	Terminal
GEL51913	BMW with ABS	12	21 AH (c20)	300 A (EN)	183	78	171	0	G
GEL53030	C60-N30L-A, 53030	12	30 AH (c20)	400 A (EN)	178	124	166	0	G
GEL53034	C60-N30-A, 53034	12	30 AH (c20)	400 A (EN)	178	124	166	1	G

Product line: 12 V gel types
Model: Completely maintenance free – gel technology
Status: GUG = Filled and charged
Quality: OEM quality
Accessories: Connection screws

Properties: Outstanding starting performance, durable, safe and reliable
Use: Motor scooters – motorcycles – ATVs/quads – jet skis – ride on lawnmowers – snowmobiles